

SKU # RS40TEMPLB

Part # 1007572

Description

40in RoadRunner SAE Compliant 210-watt LED Single Row Stealth Light Bar with MELT Temp Control System and screw-less frame construction

Categories LED Light Bars

Sub-Categories ROADRUNNER SERIES ON-ROAD COMPLIANT LIGHT BARS

UPC 810077230169

Unit of Measure EA

Related Skus:

RS7TEMPFM, RS3TEMPCL, RS6TEMPAL

Cross Sell Skus:

RS6TEMPAL,RS3TEMPCL,RS7TEMPFM

$\overline{}$			- 1	٠.			
	\cap	n	വ	п	П	\smallfrown	n
C	U	ш	u	ш	30	U	ш

Manufacturer

EZ Category

New

Race Sport Lighting

RoadRunner Series

Harmonization Code

Universal

Life Expectancy

8512.20.2080

YES

50,000 hours

SEMA Product Off-Road Light

Part Type ID 15431

Reverse Polarity

Operating Voltage

10-30VDC

Current Draw

Off-Road Light

Wattage

Chip Type

IP Rating

210-Watts

OSRAM

IP67

2,526 lx

Kelvin (ColorTemperature)

Universal or Vehicle Specific

5,700K

Lumens 9,499 lm

Universal

Beam **Pattern**

Spot

Made In Warranty CN 5 year

Product Information

Introducing the Race Sport Lighting RoadRunner SAE Compliant Single Row Stealth Light Bar - the pinnacle of lighting technology, engineered for the most demanding on-road automotive enthusiasts and off-road adventurers. With cutting-edge features like the MELT Temp Control System and screw-less frame construction, this light bar redefines excellence in illumination and durability. Illuminate the Road with Confidence: Our RoadRunner light bar is the embodiment of innovation and performance, meticulously designed to provide exceptional brightness and endurance. Whether you're conquering rugged trails or enhancing your vehicle's aesthetics, this light bar is your ultimate companion. MELT Temp Control System: Race Sport Lighting leads the industry in safety and performance with the revolutionary MELT Temp Control System. This advanced technology ensures that your light bar operates optimally, even under extreme conditions. Its advanced technology heats the lens cover and melts off snow

Est. Labor	1 Hours		
Gross Weight	6.60	Width	4.25
Net Weight	6.60	Height	4.25
DIM Weight	5.78	Depth	44.50